

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Patent Application for:

EMBEDDED CONTENT CACHING FOR INTERACTIVE TELEVISION

**Inventor(s):** Peter Rae Shintani, Aditya Krishnan, Matthew S. Chang,  
Andrew M. Proehl, David K. L. Yang, Fredrick J. Zustak, Mark  
Kenneth Eyer, Nicholas Colsey, Brant L. Candelore and Dayan  
Ivy Golden

**Docket Number:** SNY-P1465

**Prepared By:** Miller Patent Services  
29 Seminole Drive  
Ringwood, NJ 07456  
  
Phone: (973) 728-2760  
Fax: (973) 728-0438  
Email: miller@patent-inventions.com

**CERTIFICATE OF EXPRESS MAILING FOR NEW PATENT APPLICATION**

"Express Mail" mailing label number EK555538623US

Date of Deposit 1-16-2001

I hereby certify that this paper or fee is being deposited with the United States Postal Service "Express Mail Post Office to Addressee" service under 37 CFR 1.10 on the date indicated above and is addressed to the Assistant Commissioner for Patents, Washington, D C. 20231

Catherine N. Miller

(Typed or printed name of person mailing paper or fee)

Catherine N. Miller

(Signature of person mailing paper or fee)

1  
2  
3  
4  
5  
6  
7 **EMBEDDED CONTENT CACHING FOR INTERACTIVE TELEVISION**  
8  
9

10  
11 **FIELD OF THE INVENTION**

12 This invention relates generally to the field of interactive television. More  
13 particularly, this invention relates to a method and apparatus for caching interactive  
14 content for rapid access by a user.  
15

16 **BACKGROUND OF THE INVENTION**

17 Interactive television is currently available from Wink Communications of  
18 Alameda, California. Other interactive television services are also expected to be  
19 available in the near future. In accordance with one expected scenario, a universal  
20 resource locator (URL) may be incorporated as interactive content within a  
21 television program. In this scenario, when the user wishes to obtain additional  
22 information associated with the URL, he or she actuates a switch on his remote  
23 controller to retrieve a web page or other content identified by the universal  
24 resource locator. A service provider then downloads the page corresponding to the  
25 URL.

26 In order for this process to provide a useful interactive experience to the user,  
27 it is desirable that the downloading of the page corresponding to the URL occur as  
28 quickly as possible. Accordingly, the present invention addresses this need.  
29

## SUMMARY OF THE INVENTION

The present invention relates generally to interactive television. Objects, advantages and features of the invention will become apparent to those skilled in the art upon consideration of the following detailed description of the invention.

In one embodiment of the present invention an interactive television system uses a cache memory system that mirrors pages associated with a URL embedded within the interactive content. When a subscriber chooses to download the page associated with the interactive content, a server first searches the cached pages to determine if the requested pages can be downloaded to the subscriber from cache memory. If not, the requested pages are downloaded via the Internet. In another embodiment, the cache memory can be situated at a subscriber's set-top box.

A method of providing enhanced performance in an interactive television system consistent with embodiments of the present invention includes: scanning an interactive content bearing program for a universal resource locator (URL); upon finding a URL in the interactive content bearing program, mirroring content associated with the URL to a cache memory; presenting the interactive content bearing program to a plurality of subscribers; receiving a request from a subscriber for the URL; retrieving the mirrored content associated with the URL from the cache memory; and delivering the mirrored content associated with the URL to the subscriber.

The above summaries are intended to illustrate exemplary embodiments of the invention, which will be best understood in conjunction with the detailed description to follow, and are not intended to limit the scope of the appended claims.

## BRIEF DESCRIPTION OF THE DRAWINGS

The features of the invention believed to be novel are set forth with particularity in the appended claims. The invention itself however, both as to

1 organization and method of operation, together with objects and advantages  
2 thereof, may be best understood by reference to the following detailed description  
3 of the invention, which describes certain exemplary embodiments of the invention,  
4 taken in conjunction with the accompanying drawings in which:

5 **FIGURE 1** is a system block diagram of a system using a set-top box.

6 **FIGURE 2** is a functional block diagram of a digital set-top box suitable for  
7 use with the present invention.

8 **FIGURE 3** is a flow chart depicting a process used by a service provider to  
9 implement an embodiment of the present invention.

10 **FIGURE 4** is a flow chart depicting a process of receiving interactive content  
11 in accordance with an embodiment of the invention.

12 **FIGURE 5** is a flow chart depicting a process of receiving interactive content  
13 in accordance with another embodiment of the invention.

## 14 15 **DETAILED DESCRIPTION OF THE INVENTION**

16 While this invention is susceptible of embodiment in many different forms,  
17 there is shown in the drawings and will herein be described in detail specific  
18 embodiments, with the understanding that the present disclosure is to be  
19 considered as an example of the principles of the invention and not intended to limit  
20 the invention to the specific embodiments shown and described. In the description  
21 below, like reference numerals are used to describe the same, similar or  
22 corresponding parts in the several views of the drawings.

23 Referring to **FIGURE 1**, a block diagram for an exemplary interactive cable  
24 or satellite television (TV) system 100 is shown. The system 100 includes, at a  
25 head end of the service provider 10, a media server 12 for providing, on demand,  
26 movies and other programming obtained from a media database 14. The media  
27 server 12 might also provide additional content such as interviews with the actors,  
28 games, advertisements, available merchandise, associated Web pages, interactive  
29 games and other related content. The system 100 also includes an electronic

1 programming guide (EPG) server 16 and a program listing database 18 for  
2 generating an EPG. Set-top box 22 can generally provide for bidirectional  
3 communication over a transmission medium 20 in the case of a cable STB 22. In  
4 other embodiments, bidirectional communication can be effected using  
5 asymmetrical communication techniques possibly using dual communication  
6 media - - one for the uplink and one for the downlink. In any event, the STB 22 can  
7 have its own Universal Resource Locator (URL) or IP address or other unique  
8 identifier assigned thereto to provide for addressability by the head end and users  
9 of the Internet.

10 The media server 12 and EPG server 16 are operatively coupled by  
11 transmission medium 20 to a set-top box (STB) 22. The transmission medium 20  
12 may include, for example, a conventional coaxial cable network, a fiber optic cable  
13 network, telephone system, twisted pair, a satellite communication system, a radio  
14 frequency (RF) system, a microwave system, other wireless systems, a  
15 combination of wired and wireless systems or any of a variety of known electronic  
16 transmission mediums. In the case of a cable television network, transmission  
17 medium 20 is commonly realized at the subscriber's premises as a coaxial cable  
18 that is connected to a suitable cable connector at the rear panel of the STB 22. In  
19 the case of a Direct Satellite System (DSS), the STB 22 is often referred to as an  
20 Integrated Receiver Decoder (IRD). In the case of a DSS system, the transmission  
21 medium is a satellite transmission at an appropriate microwave band. Such  
22 transmissions are typically received by a satellite dish antenna with an integral Low  
23 Noise Block (LNB) that serves as a down-converter to convert the signal to a lower  
24 frequency for processing by the STB 22.

25 The exemplary system 100 further includes a TV 24, such as a digital  
26 television, having a display 26 for displaying programming, an EPG, etc. The STB  
27 22 may be coupled to the TV 24 and various other audio/visual devices 26 (such as  
28 audio systems, Personal Video Recorders (PVRs), Video Tape Recorders (VTRs),  
29 Video Cassette Recorders (VCRs) and the like), storage devices (e.g., hard disc  
30 drives) and Internet Appliances 28 (such as email devices, home appliances,

1 storage devices, network devices, and other Internet Enabled Appliances) by an  
2 appropriate interface 30, which can be any suitable analog or digital interface. In  
3 one embodiment, interface 30 conforms to an interface standard such as the  
4 Institute of Electrical and Electronics Engineers (IEEE) 1394 standard, but could  
5 also be wholly or partially supported by a DVI interface (Digital Visual Interface -  
6 Digital Display Working Group, [www.ddwg.org](http://www.ddwg.org)) or other suitable interface.

7 The STB 22 may include a central processing unit (CPU) such as a  
8 microprocessor and memory such as Random Access Memory (RAM), Read Only  
9 Memory (ROM), flash memory, mass storage such as a hard disc drive, floppy disc  
10 drive, optical disc drive or may accommodate other electronic storage media, etc.

11 Such memory and storage media is suitable for storing data as well as instructions  
12 for programmed processes for execution on the CPU, as will be discussed later.  
13 Information and programs stored on the electronic storage media or memory may  
14 also be transported over any suitable transmission medium such as that illustrated  
15 as 20. STB 22 may include circuitry suitable for audio decoding and processing,  
16 the decoding of video data compressed in accordance with a compression  
17 standard such as the Motion Pictures Experts Group (MPEG) standard and other  
18 processing to form a controller or central hub. Alternatively, components of the  
19 STB 22 may be incorporated into the TV 24 itself, thus eliminating the STB 22.  
20 Further, a computer having a tuner device and modem may be equivalently  
21 substituted for the TV 24 and STB 22.

22 By way of example, the STB 22 may be coupled to devices such as a  
23 personal computer, video cassette recorder, camcorder, digital camera, personal  
24 digital assistant and other audio/visual or Internet related devices. In addition, a  
25 data transport architecture, such as that set forth by an industry group which  
26 includes Sony Corporation and known as the Home Audio-Video Interoperability  
27 (HAVi) architecture may be utilized to enable interoperability among devices on a  
28 network regardless of the manufacturer of the device. This forms a home network  
29 system wherein electronic devices and Internet appliances are compatible with  
30 each other. The STB 22 runs an operating system suitable for a home network

1 system such as Sony Corporation's AperiOS™ real time operating system. Other  
2 operating systems could also be used.

3 The STB 22 includes an infrared (IR) receiver 34 for receiving IR signals from  
4 an input device such as remote control 36. Alternatively, it is noted that many other  
5 control communication methods may be utilized besides IR, such as wired or  
6 wireless radio frequency, etc. In addition, it can be readily appreciated that the  
7 input device 36 may be any device suitable for controlling the STB 22 such as a  
8 remote control, personal digital assistant, laptop computer, keyboard or computer  
9 mouse. In addition, an input device in the form of a control panel located on the TV  
10 24 or the STB 22 can be provided.

11 The STB 22 may also be coupled to an independent service provider (ISP)  
12 host 38 by a suitable connection including dial-up connections, DSL (Digital  
13 Subscriber Line) or the same transmission medium 20 described above (e.g., using  
14 a cable modem) to, thus, provide access to services and content from the ISP and  
15 the Internet. The ISP host 38 provides various content to the user that is obtained  
16 from a content database 42. STB 22 may also be used as an Internet access  
17 device to obtain information and content from remote servers such as remote  
18 server 48 via the Internet 44 using host 38 operating as an Internet portal, for  
19 example. In certain satellite STB environments, the data can be downloaded at  
20 very high speed from a satellite link, with asymmetrical upload speed from the set-  
21 top box provided via a dial-up or DSL connection.

22 While the arrangement illustrated in **FIGURE 1** shows a plurality of servers  
23 and databases depicted as independent devices, any one or more of the servers  
24 can operate as server software residing on a single computer. Moreover, although  
25 not explicitly illustrated, the servers may operate in a coordinated manner under  
26 centralized or distributed control to provide multiple services as a Multiple Service  
27 Operator (MSO) in a known manner. Additionally, the services provided by the  
28 servers shown in **FIGURE 1** may actually reside in other locations, but from the  
29 perspective of the user of STB 22, the service provider 10 serves as a portal to the

1 services shown. Those skilled in the art will appreciate that the illustration of  
2 **FIGURE 1** represents a simplified depiction of a cable system configuration shown  
3 simply as service provider 10. The actual configuration of the service provider's  
4 equipment is more likely to follow a configuration defined by the CableLabs  
5 OpenCable™ specification. The simplified illustration shown is intended to simplify  
6 the discussion of the service provider 10's operation without unnecessarily  
7 burdening the discussion with architectural details that will be evident to those  
8 skilled in the art. Those details can be found in the publicly available CableLabs  
9 OpenCable™ specification or in the text "OpenCable Architecture (Fundamentals)"  
10 by Michael Adams, Cisco Press, Nov. 1999.

11 Referring now to **FIGURE 2**, a typical system configuration for a digital set-  
12 top box 22 is illustrated. In this exemplary set-top box, the transmission medium  
13 20, such as a coaxial cable, is coupled by a suitable interface through a diplexer  
14 102 to a tuner 104. Tuner 104 may, for example, include a broadcast in-band tuner  
15 for receiving content, an out-of-band (OOB) tuner for receiving data transmissions.  
16 A return path through diplexer 102 provides an OOB return path for outbound data  
17 (destined for example for the head end). A separate tuner (not shown) may be  
18 provided to receive conventional RF broadcast television channels. Modulated  
19 information formatted, for example, as MPEG-2 information is then demodulated  
20 at a demodulator 106. The demodulated information at the output of demodulator  
21 106 is provided to a demultiplexer and descrambler circuit 110 where the  
22 information is separated into discrete channels of programming. The programming  
23 is divided into packets, each packet bearing an identifier called a Packet ID (PID)  
24 that identifies the packet as containing a particular type of data (e.g., audio, video,  
25 data). The demodulator and descrambler circuit 110 also decrypts encrypted  
26 information in accordance with a decryption algorithm to prevent unauthorized  
27 access to programming content, for example.

28 Audio packets from the demultiplexer 110 (those identified with an audio  
29 PID) are decrypted and forwarded to an audio decoder 114 where they may be



converted to analog audio to drive a speaker system (e.g., stereo or home theater multiple channel audio systems) or other audio system 116 (e.g., stereo or home theater multiple channel amplifier and speaker systems) or may simply provide decoded audio out at 118. Video packets from the demultiplexer 110 (those identified with a video PID) are decrypted and forwarded to a video decoder 122. In a similar manner, data packets from the demultiplexer 110 (those identified with a data PID) are decrypted and forwarded to a data decoder 126.

Decoded data packets from data decoder 126 are sent to the set-top box's computer system via the system bus 130. A central processing unit (CPU) 132 can thus access the decoded data from data decoder 126 via the system bus 130. Video data decoded by video decoder 122 is passed to a graphics processor 136, which is a computer optimized to processes graphics information rapidly. Graphics processor 136 is particularly useful in processing graphics intensive data associated with Internet browsing, gaming and multimedia applications such as those associated with MHEG (Multimedia and Hypermedia information coding Experts Group) set-top box applications. It should be noted, however, that the function of graphics processor 136 may be unnecessary in some set-top box designs having lower capabilities, and the function of the graphics processor 136 may be handled by the CPU 132 in some applications where the decoded video is passed directly from the demultiplexer 110 to a video encoder. Graphics processor 136 is also coupled to the system bus 130 and operates under the control of CPU 132.

Many set-top boxes such as STB 22 may incorporate a smart card reader 140 for communicating with a so called "smart card," often serving as a Conditional Access Module (CAM). The CAM typically includes a central processor unit (CPU) of its own along with associated RAM and ROM memory. Smart card reader 140 is used to couple the system bus of STB 22 to the smart card serving as a CAM (not shown). Such smart card based CAMs are conventionally utilized for authentication of the user and authentication of transactions carried out by the user as well as authorization of services and storage of authorized cryptography keys.

1 For example, the CAM can be used to provide the key for decoding incoming  
2 cryptographic data for content that the CAM determines the user is authorized to  
3 receive.

4 STB 22 can operate in a bidirectional communication mode so that data and  
5 other information can be transmitted not only from the system's head end to the  
6 end user, or from a service provider to the end user of the STB 22, but also, from  
7 the end user upstream using an out-of-band channel. In one embodiment, such  
8 data passes through the system bus 130 to a modulator 144 through the diplexer  
9 102 and out through the transmission medium 20. This capability is used to  
10 provide a mechanism for the STB 22 and/or its user to send information to the head  
11 end (e.g., service requests or changes, registration information, etc.) as well as to  
12 provide fast outbound communication with the Internet or other services provided  
13 at the head end to the end user.

14 Set-top box 22 may include any of a plurality of I/O (Input/Output) interfaces  
15 represented by I/O interfaces 146 that permit interconnection of I/O devices to the  
16 set-top box 22. By way of example, and not limitation, a serial RS-232 port 150 can  
17 be provided to enable interconnection to any suitable serial device supported by the  
18 STB 22's internal software. Similarly, communication with appropriately compatible  
19 devices can be provided via an Ethernet port 152, a USB (Universal Serial Bus) port  
20 154, an IEEE 1394 (so-called firewire™ or i-link™) or IEEE 1394 wide port 156, S-  
21 video port 158 or infrared port 160. Such interfaces can be utilized to interconnect  
22 the STB 22 with any of a variety of accessory devices such as storage devices,  
23 audio / visual devices 26, gaming devices (not shown), Internet Appliances 28, etc.

24 I/O interfaces 146 can include a modem (be it dial-up, cable, DSL or other  
25 technology modem) having a modem port 162 to facilitate high speed or alternative  
26 access to the Internet or other data communication functions. In one preferred  
27 embodiment, modem port 162 is that of a DOCSIS (Data Over Cable System  
28 Interface Specification) cable modem to facilitate high speed network access over  
29 a cable system, and port 162 is appropriately coupled to the transmission medium  
30 20 embodied as a coaxial cable. Thus, the STB 22 can carry out bidirectional

1 communication via the DOCSIS cable modem with the STB 22 being identified by  
2 a unique IP address. The DOCSIS specification is publically available.

3 A PS/2 or other keyboard / mouse / joystick interface such as 164 can be  
4 provided to permit ease of data entry to the STB 22. Such inputs provide the user  
5 with the ability to easily enter data and/or navigate using pointing devices. Pointing  
6 devices such as a mouse or joystick may be used in gaming applications.

7 Of course, STB 22 also may incorporate basic video outputs 166 that can be  
8 used for direct connection to a television set such as 24 instead of (or in addition  
9 to) an IEEE 1394 connection such as that illustrated as 30. In one embodiment,  
10 Video output 166 can provide composite video formatted as NTSC (National  
11 Television System Committee) video. In some embodiments, the video output 166  
12 can be provided by a direct connection to the graphics processor 136 or the  
13 demultiplexer / descrambler 110 rather than passing through the system bus 130  
14 as illustrated in the exemplary block diagram. S-Video signals from output 158 can  
15 be similarly provided without passing through the system bus 130 if desired in other  
16 embodiments.

17 The infrared port 160 can be embodied as an infrared receiver 34 as  
18 illustrated in **FIGURE 1**, to receive commands from an infrared remote control 36,  
19 infrared keyboard or other infrared control device. Although not explicitly shown,  
20 front panel controls may be used in some embodiments to directly control the  
21 operation of the STB 22 through a front panel control interface as one of interfaces  
22 146. Selected interfaces such as those described above and others can be  
23 provided in STB 22 in various combinations as required or desired.

24 STB 22 will more commonly, as time goes on, include a disc drive interface  
25 170 and disc drive mass storage 172 for user storage of content and data as well  
26 as providing storage of programs operating on CPU 132. STB 22 may also include  
27 floppy disc drives, CD ROM drives, CD R/W drives, DVD drives, etc. CPU 132, in  
28 order to operate as a computer, is coupled through the system bus 130 (or through  
29 a multiple bus architecture) to memory 176. Memory 178 may include a  
30 combination any suitable memory technology including Random Access Memory

1 (RAM), Read Only Memory (ROM), Flash memory, Electrically Erasable  
2 Programmable Read Only Memory (EEPROM), etc.

3 While the above exemplary system including STB 22 is illustrative of the  
4 basic components of a digital set-top box suitable for use with the present  
5 invention, the architecture shown should not be considered limiting since many  
6 variations of the hardware configuration are possible without departing from the  
7 present invention. The present invention could, for example, also be implemented  
8 in more advanced architectures such as that disclosed in U.S. Patent Application  
9 Serial No. 09/473,625, filed Dec. 29, 1999, Docket No. SONY-50N3508 entitled  
10 "Improved Internet Set-Top Box Having and In-Band Tuner and Cable Modem" to  
11 Jun Maruo and Atsushi Kagami. This application describes a set-top box using a  
12 multiple bus architecture with a high level of encryption between components for  
13 added security. This application is hereby incorporated by reference as though  
14 disclosed fully herein.

15 In general, during operation of the STB 22, an appropriate operating  
16 system 180 such as, for example, Sony Corporation's AperiOS™ real time operating  
17 system is loaded into, or is permanently stored in, active memory along with the  
18 appropriate drivers for communication with the various interfaces. In other  
19 embodiments, other operating systems such as Microsoft Corporation's Windows  
20 CE™ could be used without departing from the present invention. Along with the  
21 operating system and associated drivers, the STB 22 usually operates using  
22 browser software 182 in active memory or may permanently reside in ROM,  
23 EEPROM or Flash memory, for example. The browser software 182 typically  
24 operates as the mechanism for viewing not only web pages on the Internet, but  
25 also serves as the mechanism for viewing an Electronic Program Guide (EPG)  
26 formatted as an HTML document. The browser 182 can also provide the  
27 mechanism for viewing normal programming (wherein normal programming is  
28 viewed as an HTML video window - often occupying the entire area of screen 26).

29 STB software architectures vary depending upon the operating system.  
30 However, in general, all such architectures generally include, at the lowest layer,

1 various hardware interface layers. Next is an operating system layer as previously  
2 described. The software architectures of modern STB have generally evolved to  
3 include a next layer referred to as "middleware." Such middleware permits  
4 applications to run on multiple platforms with little regard for the actual operating  
5 system in place. Middleware standards are still evolving at this writing, but are  
6 commonly based upon Javascript and HTML (hypertext Markup Language) virtual  
7 machines. At the top layer is the application layer where user applications and the  
8 like reside (e.g., browsing, email, EPG, Video On Demand (VOD), rich multimedia  
9 applications, pay per view, etc.). The current invention can be utilized with any  
10 suitable set-top box software and hardware architecture.

11 Referring back to **FIGURE 1**, in accordance with certain embodiments of the  
12 present invention, media server 12 incorporates an interactive content cache 70.  
13 Interactive content cache 70 is utilized, under program control from a processor  
14 within media server 12, to store web pages or other interactive content associated  
15 with a URL, as will be clear upon considering the foregoing description. The term  
16 "cache memory" as used herein is intended to embrace any storage device, be it  
17 silicon memory, disc storage or whatever, used as a cache without limitation.

18 When interactive content is delivered to a user from the service provider 10  
19 via his set-top box 22, the interactive content may include a universal resource  
20 locator (URL) serving as a link to additional interactive content such as a web page.  
21 Upon actuating a button on remote controller 36, the user is directed to the  
22 interactive content by virtue of the interactive content associated with the URL being  
23 downloaded to the set-top box 22 for viewing by the user. In this embodiment, the  
24 user may be alerted to the presence of interactive content by virtue of being  
25 presented with various indicia on the television screen (for example an icon). Since  
26 many viewers of a particular interactive television program will likely wish to see the  
27 interactive content at approximately the same time (i.e., during or immediately after  
28 viewing the entertainment content), a data flow bottleneck can occur. Accordingly,  
29 the present invention utilizes an interactive content cache 70 to enhance the

1 performance of the system when users are downloading content associated with  
2 a particular URL.

3 This process is illustrated in the flow chart of **FIGURE 3** as process 300,  
4 which can be carried out by a programmed processor residing at the service  
5 provider head end (e.g., media server 12). This process starts at 304, after which  
6 a service provider receives entertainment content containing interactive content at  
7 308. At 314 the service provider 10 scans the entertainment content for embedded  
8 URLs in the interactive content. The scanning process continues until the end of  
9 the content is reached at 320. When a URL is found at 324, the URL is  
10 downloaded via the Internet 44 to the interactive content cache 70 at 328 and  
11 appropriately indexed for retrieval. The scanning can take place any time prior to  
12 or during presentation of the interactive content to the viewers.

13 Once the end of the entertainment content is reached at 320, the  
14 downloaded web pages or other content corresponding to the URLs found  
15 embedded in the interactive content are retained in the interactive content cache  
16 until needed as a result of a request from a subscriber set-top box. The interactive  
17 content cache 70 is purged in accordance with any suitable algorithm for purging  
18 a cache memory at 334. For example, the cache may be purged after a particular  
19 period of time has been reached (for example six to 12 hours, by which time most  
20 viewers of the interactive content who are interested will have already downloaded  
21 the interactive content associated with the URL). In other embodiments, the cache  
22 may be purged based upon a fixed size for the cache and in accordance with the  
23 order the information was placed in the cache (e.g., using a first in first-out  
24 algorithm). Thus, when the maximum size of the cache has been reached, the  
25 earliest stored material is discarded. In other embodiments, a least frequent use  
26 or any other suitable cache purging algorithm can be used. When new content is  
27 received at 340, the process begins again at 314.

28 In an extension to this concept, further pre-emptive caching can be carried  
29 out to further enhance the responsiveness of the system. In many instances, a web  
30 page or other content associated with a particular URL that appears within the

1 television programming may lead the user to another URL embedded within the  
2 web page or other content (a secondary URL). This enhances the likelihood that  
3 a user will also wish to access the secondary URL embedded within the web page  
4 or other content. Accordingly, even further enhancement to the system's  
5 performance can be obtained by mirroring or caching sites associated with such  
6 secondary URLs. This can be done at 328 by examining the cached web page  
7 associated with the URL for secondary URLs and caching those pages, or  
8 alternatively, by caching such secondary URLs after the secondary or primary URL  
9 is accessed by a user.

10 Referring now to **FIGURE 4**, the process carried out in the current  
11 embodiment for downloading the Content associated with the URL to the user of  
12 the set-top box 22 is illustrated. This process begins at 404, after which the user  
13 views entertainment content with an embedded URL at 408. At 414 the user  
14 selects the URL for downloading, and at 422 set-top box 22 sends a request to the  
15 service provider 10 for the page or other content associated with the URL (e.g.,  
16 using a cable modem). The service provider, using a programmed processor,  
17 checks for the Content associated with the URL in the interactive content cache 70  
18 at 426. If the Content associated with the URL is present in the interactive content  
19 cache 70 at 430, the Content associated with the URL is sent to the set-top box at  
20 438 (e.g., via cable modem), and the Content associated with the URL is displayed  
21 on display 26 at 444. The process ends at 448. In the event of the Content  
22 associated with the URL requested is not present at 430, the service provider head  
23 end downloads the Content associated with the URL from the Internet at 434, and  
24 control returns to 438. As previously described, secondary URLs can also be  
25 cached at 438 or upon access by a first user.

26 In an alternative embodiment, the URL associated with the interactive  
27 content may be stored in a local cache, for example forming a part of disk drive 172  
28 or memory 176, of the set-top box 22. In this embodiment, process 300 as  
29 illustrated in **FIGURE 3** is modified only in that the downloading of the Content

1 associated with the URL to cache at 328 is carried out to a local cache in set-top  
2 box 22. The download of the page to the STB cache can be carried out using a  
3 data channel and cable modem, for example. With reference to **FIGURE 5**, a  
4 process 500 is illustrated in which the user retrieves selected Content associated  
5 with the URL from local cache. The process starts at 504, after which the user  
6 views entertainment content with an embedded URL at 508. At 514 the user  
7 selects the URL for display of associated information. At 522 set-top box checks  
8 for the Content associated with the URL in the local interactive content cache of,  
9 for example disk drive 172. If the Content associated with the URL is present at  
10 528, the Content associated with the URL is displayed at 534 and the process ends  
11 at 538.

12 If the Content associated with the URL is not present at 528, the Content  
13 associated with the URL is requested from the service provider 10 at 544. The  
14 service provider checks the interactive content cache 70 at 548 to determine if it  
15 contains the Content associated with the URL. If it is present at 552, the Content  
16 associated with the URL is sent to the set-top box 22 at 560 for display at 534. In  
17 the event the page is not present at 552, the Content associated with the URL is  
18 downloaded to interactive content cache 70 at 556 before sending the Content  
19 associated with the URL to the set-top box 22 at 560.

20 Those skilled in the art will find many variations of the present invention are  
21 possible without departing from the present invention. For example, Those skilled  
22 in the art will recognize that the present invention has been described in terms of  
23 exemplary embodiments based upon use of a programmed processor. However,  
24 the invention should not be so limited, since the present invention could be  
25 implemented using hardware component equivalents such as special purpose  
26 hardware and/or dedicated processors which are equivalents to the invention as  
27 described and claimed. Similarly, general purpose computers, microprocessor  
28 based computers, micro-controllers, optical computers, analog computers,  
29 dedicated processors and/or dedicated hard wired logic may be used to construct  
30 alternative equivalent embodiments of the present invention.



1           Those skilled in the art will appreciate that the program steps used to  
2           implement the embodiments described above can be implemented using disc  
3           storage as well as other forms of storage including Read Only Memory (ROM)  
4           devices, Random Access Memory (RAM) devices; optical storage elements,  
5           magnetic storage elements, magneto-optical storage elements, flash memory, core  
6           memory and/or other equivalent storage technologies without departing from the  
7           present invention. Such alternative storage devices should be considered  
8           equivalents.

9           The present invention is preferably implemented using a programmed  
10          processor executing programming instructions that are broadly described above in  
11          flow chart form and can be stored on an electronic storage medium as instructions  
12          to be carried out on a programmed processor. However, those skilled in the art will  
13          appreciate that the processes described above can be implemented in any number  
14          of variations and in many suitable programming languages without departing from  
15          the present invention. For example, the order of certain operations carried out can  
16          often be varied, and additional operations can be added without departing from the  
17          invention. Error trapping can be added and/or enhanced and variations can be  
18          made in user interface and information presentation without departing from the  
19          present invention. Such variations are contemplated and considered equivalent.

20          While the invention has been described in conjunction with specific  
21          embodiments, it is evident that many alternatives, modifications, permutations and  
22          variations will become apparent to those skilled in the art in light of the foregoing  
23          description. Accordingly, it is intended that the present invention embrace all such  
24          alternatives, modifications and variations as fall within the scope of the appended  
25          claims.

26               What is claimed is:  
27  
28